

HP Elite USB-C Docking Station



Creating a complete workspace has never been simpler

Charge your device, view content on dual displays, access a range of accessories, and connect to a desktop PC experience with a single cable connection to the HP Elite USB-C™ Docking Station.

Quick and easy connectivity enabled by USB-C™

Connect the attached cable to your tablet's USB-C™ port and get immediate connectivity to a wired network, multiple displays¹ and all of your devices—at the same time—with DisplayPort, HDMI, RJ-45, and five USB ports.

Power on

Keep working with a power pass through that powers your device while it charges.²

Universal compatibility

Use a dock that works with HP and non-HP notebooks, tablets, and desktops with a Windows® operating system.

Built for enterprise

Support network manageability³ of your device and the docking station with integrated Wake on LAN, PXE boot, and 802.1x authentication on the docking station, and get physical security from a security lock slot (lock sold separately).

Park it or pack it

Place the compact dock on your desk with minimal impact to your workspace, or take it to go with your tablet.

Rest easy

Get the reassurance of a one-year limited warranty.

¹ Sold separately.

² See product QuickSpecs for exact charging capacities.

³ Internet access required and sold separately.

Specifications



HP Elite USB-C Docking Station

Model number	T3V74AA
Dimensions (H x W x D)	6x2.76x0.77 in
152.4x70x19.6 mm	2.5 lbs (1.13 kg) w/shoulder strap
Weight	0.66 +/-0.4lbs (300+/-20g)
Normal Operating Voltage	19.5V
Average Operating Power	55 W
Max Operating Power	62 W
Temperature (Operating)	32-104 F (0-40 C)
Temperature (Non-operating)	-40 to 158 F (-40 to +70C)
Relative humidity (Operating)	5%- 95% RH , non-condensing
Relative humidity (Non-operating)	90% RH, 84.2F (29° C) maximum wet bulb temperature
Altitude (Operating)	10000 ft (3048 m)
Altitude (Non-operating)	30000 ft (9144 m)
Shock (Operating)	40 G, 2 ms, half-sine
Shock (Non-operating)	240 G, 2 ms, half-sine
Random vibration (Operating)	0.21 grms, 5 to 500 Hz, 1 hour per axis (X,Y,Z)
Random vibration (Non-operating)	2.09 grms, 5 to 500 Hz, 1 hour per axis (X,Y, Z)
Option kit contents	HP Elite USB-C Docking Station, AC power cable, 65W A/C adapter, Documentation.

Sign up for updates
hp.com/go/getupdated






Share with colleagues



Rate this document

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

